



Commercial & public fittings > Shower fittings > Shower panels > FACE MOUNTED Aluminium panel

SECURITHERM shower panel :

SPECIFICATIONS

SECURITHERM aluminium shower panel, face mounting, with PREMIX thermostatic mixing valve, electronic control with infrared presence detection, supplied by a 6V Lithium battery, with chrome plated solid brass vandal resistant shower head. Regulated flow rate 6 lpm with adjustable scale proof nozzle (can be locked on installation) and anti-scalding safety. Anti-Legionella duty flush for 60 sec every 24 hours after the last use. M1/2" back inlets with filters and non-return valves. 3 year warranty. Brand DELABIE type SECURITHERM electronic shower panel. Ref. 792410 (or approved equivalent)

Réf. : 792410 : <P>without soap dish</P>

» Soap dish available on request (see below). Floor traps available separately.



FONCTIONING AND APPLICATION

- Activates with presence detection - approach the hand 4cm away from the sensor.
- VOLUNTARY shut-off (after a second hand movement near the sensor) OR AUTOMATIC (after 1min. flow= safety delay)
- Temperature selection via thermostatic mixing valve.
- Use: recommended for all public and commercial place that prioritize comfort and safety of use

PRODUCT ADVANTAGES

- DESIGN incomparable to systems with exposed piping.
- WATER SAVING: close to 90% compared with traditional shower valves.
- HYGIENE: Anti-Legionella duty flush for 60 sec. every 24 hours after last use (automatic purge of the pipe work prevents the development of bacteria).
- RESISTANCE TO VANDALISM: unremovable by the user (hidden fixing, closed edges and rounded shape with nothing to grip).
- ANTI-SCALDING SAFETY: immediate hot water shut-off in case of cold supply failure.
- COMFORT: temperature stability regardless of pressure variations and flow rates within the installation.
- RELIABILITY: tamperproof mechanism in scale and corrosion proof materials. Self-cleaning hydraulic delay device with calibrated groove.
- LIMITED SERVICING: scale-proof nozzle.

- EASY MAINTENANCE: Interchangeable thermostatic and time flow cartridges, accessible without dismantling the shower panel.
- 3 YEAR WARRANTY.

792410

