



Markwik 21 Bib Mixer Thermomostatic, Sensor Proximity, Bioguard

Illustrated

A6061 (TB H6) Markwik 21 integral thermostat, bib mixer, proximity sensor, single flow horizontal outlet, 2 x 1/2" inlets at 200mm centres, Armitage Bioguard outlet fitted

Configuration options

Material

Chrome Plated Brass

Weights

A6061 4.91KG

Colours

Chromium plated (AA)

Standards

Conforms to HTM64 (2006), HTM04-01, HFN30.


Special Notes

This product is fitted with an Armitage Bioguard outlet which reduces the opportunity for bio film attachment and is lined with anti-microbial copper.

Tap is activated by movement in the proximity of the sensor and stops immediately when both movement and proximity stop. Unique built-in thermal disinfection cleansing feature using kit S8239NU a bridging hose which is re-usable. A purging tool A4556AA is also available to facilitate initial installation or aid in system disinfection.

* Line drawing shows recommended height over washbasin. Especially suited to medium and large hospital pattern integral back outlet basins and washing associated with clinical or nursing procedures.

Flow rate regulated to maximum of 10 Litres per minute.



Frequently used applications

General Healthcare

Hospitals

Features

HTM

Accreditations

TMV3

WRAS

*Armitage
Shanks*

Tel: 0870 122 8822
Fax: 0870 122 8282
Email: info@idealspec.co.uk
Web: www.idealspec.co.uk

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Powered by
IdealSpec

Date created: 27/02/2015