

# Aquastream<sup>®</sup> Thermo

with adjustable height head

- Thermostatic integral power shower
- Suitable for exposed or concealed pipework
- Top, bottom or rear entry
- 2 high performance flow rates – 10 litres/min and 18 litres/min
- Separate controls for flow and temperature
- Quiet, low voltage operation
- Supplied with 3 spray pattern Varispray shower kit
- 3 year comprehensive manufacturer's guarantee

## FIXING DATA

### INLETS

Gravity fed supplies only.

Must not be fitted to a mains supply.

15mm push-fit connections.

### REAR ENTRY

65mm pipe centres.

Pipe projection from finished wall is 18-22mm.

### TOP ENTRY

65mm pipe centres.

Pipe insertion depth from top of unit into top entry fitting is 160mm.

### BOTTOM ENTRY

Pipe insertion depth measured from the point of entry into the casework is 50mm at 65mm centres.

## WATER PRESSURES

Maximum: 1 bar (10 metre head).

## FLOW RATES

1m head – normal 10 ltr/min.

1m head – boost 18 ltr/min.

## TRANSFORMER

Supplied with 2 metres of mains cable and 4 metres of low voltage cable. Transformer is AC type.

## PIPEWORK

Generally 15mm throughout.

'Full way' isolating valves MUST be fitted to inlet supplies.

## ELECTRICAL INFORMATION

Fuse size 3amp in fuse spur.

## WATER SYSTEM COMPATIBILITY

Gravity  Combi  Mains fed  Unvented

## PLEASE NOTE

Do not fit the Aquastream Thermo directly to the water main.

## SITING

Easy fit template supplied.

Operates in negative head situation, but top of mixer unit must always be lower than base of cold storage cistern.

Chrome	813.40.01
White / Chrome	813.40.21
White	813.40.20

## SHOWER HEAD

MAX 355mm



## SHOWER UNIT



160mm

276mm

316mm

143mm

216mm