



AFTERCARE INSTRUCTIONS

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces.

All surface finishes will wear if not cleaned correctly, the only safe way to clean your fitting is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting even the non-scratch cleaners.

GUARANTEE

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture.

As gold and special effect finishes are softer than chromium plate, special care must be taken when cleaning, a 3 year guarantee covers these finishes.

NOTE: - the 5 year guarantee is invalidated if damaged by any waterborne debris.

PRODUCT CODE: BS1 C / ST

TELEPHONE HELP LINE! +44 (0) 870 4425553

Bristan Limited
Birch Coppice Business Park
Dordon
Tamworth
Staffordshire
B78 1SG
UK

Web site: www.bristan.com

Telephone: +44 (0) 870 4425556

Facsimile: +44 (0) 870 4425554

Email: enquire@bristan.com

(FI BS1 11/03/02 MZ)



Quadrant Bath Spout

Fitting Instructions

Please keep these instructions for future reference

For latest prices and delivery to your door visit MyTub Ltd 0845 303 8383 www.mytub.co.uk

This bath spout is intended to be used in conjunction with other products, such as the blending valves, diverters and stopcocks from the Bristan Quadrant range in order to create a system to suit your requirements.

COMPONENTS

1. Bath spout
2. Shroud
3. Backnut (optional)

INSTALLATION

The bath spout should be arranged in your system with a supply of pre-mixed water.

1. Identify all components and check for completeness, particularly before arranging fitting.
2. Depending on application the bath spout (1) can be panel mounted, using a backnut (3) or set into the wall on rigid pipe work.
3. Connect spout to pipe work in wall using recommended $\frac{3}{4}$ " BSP connections (not provided) using a thread sealing compound where necessary.

NOTE: - Before finishing wall turn on water supplies to check both correct system function and for leaking from joints/connections.

4. Complete wall finish taking care to protect fitting.
5. Fit shroud (2) over body and slide up to wall.
6. See over the page for aftercare instructions.

