AFTERCARE INSTRUCTIONS

Your fitting has a high quality finish and should be treated with care to preserve the visible surfaces. All surface finishes will wear if not cleaned correctly, the only safe way to clean your mixer is to wipe with a soft damp cloth. Stains can be removed using washing up liquid. All bath cleaning powders and liquids will damage the surface of your fitting even the non-scratch cleaners.

GUARANTEE

All products are manufactured to the highest standards and a 5 year guarantee covers any defect in manufacture. As gold and special effect finishes are softer than chromium plate, special care must be taken when cleaning; a 3 year guarantee covers these.

NOTE: The 5 year guarantee on the valves is invalidated if damaged by any waterborne debris.

In the interests of continuous product development Bristan reserve the right to alter specification as necessary.

(D3)

PRODUCT CODE: PM BSM C / SAT / ST TELEPHONE HELPLINE: 0844 701 6273

Bristan Group Ltd Birch Coppice Business Park Dordon Tamworth Staffordshire B78 1SG UK A Masco Company

Web Site: www.bristan.com Telephone: 0844 701 6273 Facsimile: 0844 701 6275 Email: enquire@bristan.com (FI PM BSM)

BRISTAN

Prism Deck Mounted Bath Shower Mixer

Fitting Instructions & Contents List

Please keep these instructions for future reference and for the request of replacement parts.


(ST)

WATER PRESSURE

This mixer is suitable for use at all supply pressures. However for optimum use both the hot and cold supplies should be reasonably balanced. If the fitting is installed at low pressure (tank fed), then the minimum height from the highest installed position of the showerhead to the underside of the cold tank should be 1 metre to ensure adequate shower performance.

This mixer should be installed in compliance with Water Regulations. Where the supplies are unbalanced, i.e. hot water from cylinder tank/cold from the mains, approved check valves must be fitted in the supply pipes. For further details contact your Local Water Authority.

CONTENTS



INSTALLATION

- Identify all components and check for completeness, particularly before arranging fitting.
- 2. Fit the mixer body to the bath using the washers (5) and backnuts (6), connect the hot and cold water supplies.
- Fit the hose (8) to the mixer (4) and the handset (9) using the small sealing washers (7).



Prior to drilling into walls, check there are no hidden electrical wires, cables or water supply pipes with the aid of an electronic detector. If you use power tools do not forget to:

- Wear eye protection
- Unplug equipment after use
- Fix the wall bracket (13) in place ensuring the handset (9) will reach.
- Fully open both valves, letting them run for a few minutes to check for leaks.
- 6. Operate the mixer in both bath and shower mode.
- To switch from bath to shower mode, pull the diverter knob (10) up. After use the mixer reverts to bath filling mode.

MAINTENANCE

If the fitting begins to drip:

- Turn off the water supply.
- Unscrew head lever (1), loosen grub screw (2) with 2.5mm hexagon key and pull off head (3).
- 3. Remove valve.
- 4. Carefully clean seating, rubber washer and ceramic disc.
- 5. Replace valve and head and turn on the water supply.
- 6. Contact our helpline if problem persists.

Please Note: In the unlikely event you find a part missing please contact our customer Service Help line on 0844 701 6273 for immediate dispatch of part.

