

N21S/5040 Obtuse street elbow, 45°.




Obtuse street elbow, 45°. female copper x male copper for insertion in fitting.

GENERAL INFORMATION

Size	Pattern No.	Box Qty	Code	Barcode	Price (£) ex VAT
10mm	N21S/5040	10	85128D	5022050149497	POA
12mm	N21S/5040	10	85129D	5022050149534	POA
15mm	N21S/5040	10	88661	5022050886613	£153.14
16mm	N21S/5040	10	85132D	5022050149695	POA
18mm	N21S/5040	10	85133D	5022050149756	POA
22mm	N21S/5040	10	88665	5022050886651	£364.42
28mm	N21S/5040	10	88667	5022050886675	£805.38
35mm	N21S/5040	1	88671	5022050886712	£2551.74
42mm	N21S/5040	1	88673	5022050886736	£4499.67
54mm	N21S/5040	1	88674	5022050886743	£7445.50

DIMENSIONS (mm)



Code	Description	a	c	Za
85128D	10mm N21S/5040	14	16	6
85129D	12mm N21S/5040	12	13	4
88661	15mm N21S/5040	17	19	6
85132D	16mm N21S/5040	19	19	8
85133D	18mm N21S/5040	20	21	7
88665	22mm N21S/5040	26	27	12
88667	28mm N21S/5040	29	30	10
88671	35mm N21S/5040	38	39	15
88673	42mm N21S/5040	42	15	46
88674	54mm N21S/5040	61	29	62

PRESSURE & TEMPERATURE

Endex (and Endbraze 67mm) performance when correctly assembled with copper tube to BS EN 1057 using tin/copper soft solder BS EN 29453 S-Sn99Cu1 or tin/silver soft solder BS EN 29453 L-SnAg5 DIN 1707

Service temperature

Size	-40° C (Min)	30° C	65° C	110° C (Max)
6mm to 28mm	25bar	25bar	25bar	16bar
35mm to 54mm	25bar	25bar	16bar	10bar
67mm	16bar	16bar	16bar	10bar

Endex (and Endbraze 67mm) performance when correctly assembled with copper tube to BS EN 1057 using tin/lead soft solder BS EN 29453 D-Pb60Sn40

Not suitable for use in potable water systems

Service temperature

Size	-15° C (Min)	30° C	65° C	110° C (Max)
6mm to 54mm	16bar	16bar	10bar	6bar
67mm	10bar	10bar	6bar	4bar

GUARANTEE

Pegler Yorkshire 25 Year Guarantee - Terms and Conditions

Products are subject to a 25 year guarantee that is between Pegler Yorkshire and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.

APPROVALS



[DVGW](#)



[BSI](#)



[Russia](#)

kiwa

[KIWA Gastec](#)



[CSN](#)



[WRAS](#)

kiwa

[KIWA](#)