
Product Data Sheet





Contour 21 Back To Wall Rimless Raised Height WC Pan, 70cm projection

Illustrated

S3617

S3115 (WC H) Contour 21 back to wall rimless raised height WC pan with floor fixing kit horizontal outlet, 70cm NHS projection

Conceala 2 cistern 4.5 or 6 litre single flush syphon side supply and internal overflow plastic flushbend, long CP

supply and internal overflow plastic flushbend, long C lever

S4066 Contour 21 seat no cover, top fixing hinges and retaining buffers

S6481 Contour 21 back support rail for 70cm projection HTM64 WC, 40 x 17 x 35mm diameter tube

S6884 Cushion for back support with clips, new designS4302 Contour 21 flushpipe constructed, necessary for

installation

Configuration options

S3640 Conceala 2 cistern 4.5 litre single flush valve side supply and internal overflow, alternative height plastic flushbends

S3643 Conceala 2 cistern 4.5/3 litre dual flush valve side supply and internal overflow, alternative height plastic flushbends, no flushplate

S3599 Sensorflow 21 WC flushing device, panel mounted sensor complete with concealed valve and4 or 4.5 litre duct cistern

S4512 Finger push button pneumatic, stainless steel for 31mm maximum thickness partition

S4513 Palm push button Pneumatic, stainless steel for 31mm maximum thickness partition

S4504 Contemporary flush plate dual flush, Armitage Shanks logo, stainless steel for Conceala 2 cisterns

S4300 Panekta outlet Connector, finned pattern to convert horizontal outlet WCs to S or turned P trap

S4305 Panekta outlet Connector, finned pattern to convert horizontal outlet WCs to P trap

Material

Vitreous China

Weights

\$3115 31.05KG \$3617 3.00KG \$4066 1.55KG \$6481 0.85KG \$6884 4.00KG \$4302 0.39KG

Colours

White (01)

Standards

Vitreous china to BS 3402

Special Notes

Lever cistern fittings are reversible.

WC screwed to floor using floor fixing kit (supplied) & cistern screwed to wall.

Designer

Robin Levien, RDI

Frequently used applications

Hospitals

Features

нтм

Special Care Water Saving

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

Email: info@idealspec.co.uk

Web: www.idealspec.co.uk

Tel: 0870 122 8822

Fax: 0870 122 8282

Armitage

