

TECHNICAL DATA SHEET

MANHATTAN MANHATTAN MONOBLOC SINK MIXER

Product Specification

Product Code:	MH SNK C (As shown) MH SNK WHT MH SNK MOC MH SNK BGE
Finishes:	Chrome, White, Mocca, Beige
Product Type:	Contemporary
Construction:	Bodies are of all brass construction and are designed to conform to BS EN 200
Cartridge/Valve Type:	Ceramic disc valves
Supply:	Suitable for all plumbing systems
Inlet Connections:	15mm copper tail pipes
Water Pressure:	Min. 0.2 bar, Max. 8.0 bar



Additional Information

- Dual flow
- Chrome plated to BS EN 248
- Supplied with 15mm copper tail pipes
- Compatible with the following flow limiters: ECO TAP1
ECO TAP2
ECO TAP3
ECO TAP4
ECO TAP5
ECO TAP6
- Flow limiters have to be fitted into a 15mm compression fitting

Technical Advice: For further information please call 0844 7016273 or email customer@bristan.com.
Guarantee: 5 years covering manufacturing faults.

Compliance/Approvals

WRAS: Manufactured to comply with WRAS

Flow Rates (litres per min.)

System Pressure	0.2bar	0.5bar	1bar	2bar	3bar	5bar
MH SNK	4.1	7.2	10.4	14.9	18.6	24.1

