## **TECHNICAL DATASHEET**



# **Jute**Jute Bath Shower Mixer

### **Product**Specification

Product Code: JU BSM E6 C, JU BSM E8 C

Finish: Chrome Plated Product Type: Contemporary

**Construction:** Body is of brass construction and

is designed to conform to BS EN 200.


Valve Type: 3/4", 1/4 turn ceramic disc valves

Supply: Suitable for all plumbing systems (Preferably balanced)

Inlet Connections: 34" BSP Outlet Connection: 6 1/2"

Working Pressures: Min 0.2bar, Max 8.0bar Dimensions for Fitting: 180mm inlet centres





1500mm HOSE, RUB CLEAN HANDSET & WALL BRACKET

#### AdditionalInformation

- Supplied with metal handles
- Chrome plated to BS EN 248
- Supplied with single function rub clean handset, 1.5m hose & wall bracket
- Product supplied with either a 6 or 8 litre per minute flow regulator which can be fitted to the shower hose outlet to reduce water consumption and increase water efficiency (Flow Regulator accurate +/- 10%).

**Technical Advice:** For further information please call 0844 7016273 or email

customercare@bristan.com

**Guarantee:** 5 years covering manufacturing faults.

#### Compliance/Approvals

Manufactured to comply with WRAS

FlowRates (litres per minute)

SystemPressure	<b>0.2</b> bar	<b>0.5</b> bar	1bar	2bar	3bar	<b>5</b> bar
To Bath Fill	20.7	34.2	48.9	69.4	85.0	
Without Flow Regulator Fitted (To Shower Outlet)	3.1	5.5	8.3	12.5	16.5	
With 6 l/p/m Flow Regulator Fitted (To Shower Outlet)			6.0	6.0	6.0	6.0
With 8 l/p/m Flow Regulator Fitted (To Shower Outlet)			8.0	8.0	8.0	8.0







Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG Telephone: 0844 701 6274 Facsimile: 0844 701 6275 Web Site: <a href="https://www.bristan.com">www.bristan.com</a> Email: <a href="mailto:enquire@bristan.com">enquire@bristan.com</a>

D1
The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.