## **TECHNICAL DATA SHEET**



## ORB DUAL CONTROL RANGE ORB SHCDIV C

## **Product** Specification

Product Code: ORB SHCDIV C
Finish: Chrome
Product Type: Contemporary

Construction: Body is of brass construction and is

designed to conform to BS EN 2000

Cartridge Type: Ceramic disc valve

**Supply:** Suitable for all plumbing conditions,

preferably balanced. The inlet hot water temperature must be at least 10% above the required blend

temperature.

Inlet Connections: 15mm Compression connections
Working Pressures: Working pressures 0.2-5.0 Bar

Maximum Static Pressure: 10 Bar



• Chrome plated to BS EN 248

Suitable for cavities between 58-75mm

 Minimum cold water supply temperature is 5°c

 Maximum hot water supply temperature is 80°c


 Flow rate at 0.2 Bar (open outlet without flow regulators) is 8 l/min


Requires rear access to service the filters

• Cartridge can be accessed from front









**Technical Advice:** For further information please call 0844 7016273 or email

customercare@bristan.com

**Guarantee:** 5 years covering manufacturing faults.

System Pressure	0.1bar	0.2bar	0.5bar	1.0bar	2.0bar
ORB SHCDIV C - Outlet 1	3.5	6.9	12.8	19	27.6
ORB SHCDIV C - Outlet 2	2.6	6.7	12.5	18.5	27







Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG Telephone: 0844 701 6274 Facsimile: 0844 701 6275
Web Site: <a href="https://www.bristan.com">www.bristan.com</a> Email: <a href="https://enguire@bristan.com">enguire@bristan.com</a>

D.

D1
The information contained on this page was correct at date of issue. Fitting dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.