

brassware sensorflow 21 compact spouts integral sensor

A range of sensor operated brassware with integral sensor.

Demand for hygiene and water saving is met by a range of "no touch" electronic taps, second to none.

Automatic shut off if sensor is obstructed for prolonged period.

Mains powered (transformer) with option to link up to 5 link units per main unit and independent battery powered units.

Commercial use

Hygienic "no touch" operation

Modern, no moving parts

Mains (transformer) supply or battery

DDA compliant



Illustrated

A4846AA Sensorflow 21 compact tubular 150mm wall mounted spout with integral sensor, mains

A4849AA Sensorflow 21 compact tubular 230mm wall mounted spout with integral sensor, mains

Weight

1.8kg

Options

A4847AA Sensorflow 21 compact tubular 150mm wall mounted spout with integral sensor, link (up to 5 per A4846AA)

A4845AA Sensorflow 21 compact tubular 150mm wall mounted spout with integral sensor, battery

A4850AA Sensorflow 21 compact tubular 230mm wall mounted spout with integral sensor, link (up to 5 per A4849AA)

A4848AA Sensorflow 21 compact tubular 230mm wall mounted spout with separate sensor, battery

Special notes

Designed to be supplied with pre-mixed water. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device.

The downward pointing sensor is set to work in the normal hand washing position. This helps to eliminate false triggering from high visibility clothing associated with forward facing sensors

