
TECHNICALDATASHEET ARTISAN ARTISAN THERMOSTATIC BATH SHOWER MIXER



ProductSpecification

- Product Code: Finishes: Product Type: Construction: Valve Type: Cartridge: Supply: Inlet Connections: Water Pressure:
- AR THBSM C Chrome plated Contemporary Bodies are of all brass construction 1/2" Standard valve Thermostatic Suitable for all plumbing systems, preferably balanced 3/4" BSP Min 0.2bar Max. 8.0bar



AdditionalInformation

- Dual control Flow and temperature are controlled separately giving accurate control of both
- Thermostatic control to bath and shower functions
- · Product supplied without shower kit
- Thermostatic cartridge maintains showering temperature to +/-1°C by compensating for changes in the incoming water temperature and pressure giving the stable outlet temperature
- Automatic shut off in the event of hot or cold water supply failure, thus reducing the risk of any injury
- Factory set to 38°C to eliminate the ability to select unsafe temperature, this can be overridden by user
- Chrome plated to BS EN 248

Technical Advice:	For further information please call 0844 7016273 or email customercare@bristan.com
Guarantee:	5 years covering manufacturing faults

Compliance/Approvals

WRAS:

Pending

FlowRates (litres per minute)

System Pressure	0.2bar	0.3 bar	0.4 bar	0.5 bar	1bar	3 bar	5 bar
AR THBSM C	7.40	9.96	12.60	14.36	22.78	39.27	42.40

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG Telephone: 0844 701 6274 Facsimile: 0844 701 6275 Web Site: www.bristan.com Email: enquire@bristan.com

