



Commercial & public fittings > W.C. flush valves > Self-closing flush valves > EXPOSED fittings

TEMPOFLUX WC w. integ. stop cock :

SPECIFICATIONS

Automatic shut-off direct flush valve, exposed for wall mounting, for traditional WC or children pan. Including: chrome plated solid brass body and push button, with integrated stop cock and siphon action vacuum-breaker, for angled M3/4" inlet and outlet nut Ø28, without tube. 10 years warranty. Brand DELABIE type TEMPOFLUX exposed for WC. Ref. 761000

Réf. : 761001 : with integrated stop cock and outlet nut Ø28, without tube

- » • Provide flush tube and connection washer.
- Recommended pressure: 2 to 4 bar : flow rate 1,25l./sec. at 2 bar. Inlet connection from Ø20 interior, and outlet Ø28 (brass tube) or Ø32/26 (PVC tube).



FONCTIONING AND APPLICATION

- Opening by pressing the push button.
- Automatic shut-off delay 7 sec.
- Use: public and commercial place and particularly hospitals, day nurseries, schools...

PRODUCT ADVANTAGES

- **HIGH RESISTANCE TO VANDALISM:** chrome plated solid brass body and push button and shock proof mechanism.
- **SMOOTH OPENING** adapted to children and disabled person.
- **EFFICIENCY WITHOUT SERVICING** of the direct flush (tanks are unsuitable for public sanitariums, get scaled, impurities and require a more frequent and difficult servicing).
- **RELIABILITY:** unmatched endurance, and scale, corrosion and foolproof mechanism. Self-cleaning hydraulic delay device.
- **EASY MAINTENANCE:** Interchangeable mechanism cartridge.
- **10 YEARS WARRANTY**

761001

