



## TEMPOFLUX CONCEALED for WC pan :

### SPECIFICATIONS

Automatic shut-off direct flush valve, concealed behind stainless steel wall plate Ø195, for traditional WC or children pan. Including: chrome plated solid brass body and push button, with built-in stop cock, for in-line M3/4" inlet and outlet with bush for PVC tube Ø32/26. 10 years warranty. Brand DELABIE type TEMPOFLUX concealed for WC. Ref. 761900

Réf. : 761900 : recessed under&nbsp;chrome plated&nbsp;wall plate Ø195

- » • Provide flush tube and connection washer.
- Recommended pressure: 2 to 4 bar : flow rate 1,25l./sec. at 2 bar. Inlet connection from Ø20 interior, and outlet Ø28 (brass tube) or Ø32/26 (PVC tube).



### FONCTIONING AND APPLICATION

- Opening by pressing the push button.
- Automatic shut-off delay 7 sec.
- Use: public and commercial place and particularly hospitals, day nurseries, schools...

### PRODUCT ADVANTAGES

- **HIGH RESISTANCE TO VANDALISM:** vandal proof push button control and stainless steel wall plate without visible fixing.
- **SMOOTH OPENING** adapted to children and disabled person.
- **EFFICIENCY WITHOUT SERVICING** of the direct flush (tanks are unsuitable for public sanitariums, get scaled, impurities and require a more frequent and difficult servicing).
- **RELIABILITY:** unmatched endurance, and scale, corrosion and foolproof mechanism. Self-cleaning hydraulic delay device.
- **EASY MAINTENANCE:** Interchangeable mechanism cartridge.
- **10 YEARS WARRANTY**

761900

