



Tee, reduced branch. All ends for copper.

GENERAL INFORMATION

| Size | Pattern No. | Box Qty | Code | Barcode | Price (£) ex VAT |
|-------------|-------------|---------|-------|---------------|------------------|
| 67 x 28mm | N25 | 1 | 88807 | 5022050888075 | £127.17 |
| 76 x 35mm | N25 | 1 | 89000 | 5022050890009 | £155.93 |
| 76 x 42mm | N25 | 1 | 89654 | 5022050896544 | £155.93 |
| 76 x 54mm | N25 | 1 | 89001 | 5022050890016 | £155.93 |
| 108 x 54mm | N25 | 1 | 89660 | 5022050896605 | £207.55 |
| 108 x 76mm | N25 | 1 | 89002 | 5022050890023 | £273.19 |
| 133 x 54mm | N25 | 1 | 89715 | 5022050897152 | £359.39 |
| 133 x 108mm | N25 | 1 | 89716 | 5022050897169 | £506.93 |
| 159 x 54mm | N25 | 1 | 89717 | 5022050897176 | £415.90 |
| 159 x 133mm | N25 | 1 | 89718 | 5022050897183 | £806.61 |

DIMENSIONS (mm)

| Code | Description | a | c | Za | Zc |
|-------|-----------------------|-----|-----|----|-----|
| 88807 | 67 x 67 x 28mm N25 | 54 | 66 | 19 | 47 |
| 89000 | 76 x 76 x 35mm N25 | 46 | 67 | 28 | 52 |
| 89654 | 76 x 76 x 42mm N25 | 51 | 69 | 34 | 53 |
| 89001 | 76 x 76 x 54mm N25 | 55 | 69 | 38 | 52 |
| 89660 | 108 x 108 x 54mm N25 | 61 | 90 | 39 | 73 |
| 89002 | 108 x 108 x 76mm N25 | 70 | 85 | 48 | 68 |
| 89715 | 133 x 133 x 54mm N25 | 90 | 125 | 56 | 88 |
| 89716 | 133 x 133 x 108mm N25 | 105 | 133 | 70 | 99 |
| 89717 | 159 x 159 x 54mm N25 | 90 | 145 | 55 | 110 |
| 89718 | 159 x 159 x 133mm N25 | 120 | 150 | 87 | 114 |

PRESSURE & TEMPERATURE

Endex (and Endbrazed 67mm) performance when correctly assembled with copper tube to BS EN 1057 using tin/copper soft solder BS EN 29453 S-Sn99Cu1 or tin/silver soft solder BS EN 29453 L-SnAg5 DIN 1707

Service temperature

| Size | -40° C (Min) | 30° C | 65° C | 110° C (Max) |
|--------------|--------------|-------|-------|--------------|
| 6mm to 28mm | 25bar | 25bar | 25bar | 16bar |
| 35mm to 54mm | 25bar | 25bar | 16bar | 10bar |
| 67mm | 16bar | 16bar | 16bar | 10bar |

Endex (and Endbrazed 67mm) performance when correctly assembled with copper tube to BS EN 1057 using tin/lead soft solder BS EN 29453 D-Pb60Sn40

Not suitable for use in potable water systems

Service temperature

| Size | -15° C (Min) | 30° C | 65° C | 110° C (Max) |
|-------------|--------------|-------|-------|--------------|
| 6mm to 54mm | 16bar | 16bar | 10bar | 6bar |
| 67mm | 10bar | 10bar | 6bar | 4bar |

GUARANTEE

Pegler Yorkshire 25 Year Guarantee - Terms and Conditions

Products are subject to a 25 year guarantee that is between Pegler Yorkshire and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects when installed in accordance with our instructions on specified tube materials and applications, and does not cover parts subject to normal wear and tear.

This product range has been designed for the use of homeowners, domestic and commercial applications and therefore the Guarantee is subject to the product being properly selected for their intended service conditions.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

This is reinforced where valves are covered by the European Pressure Equipment Directive (PED97/23/EC) where Installation, Operating and Maintenance Instructions are supplied with each product and/or carton.

Provided it is installed correctly and receives adequate preventative maintenance it should give years of trouble-free service.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to installation or consequential damages.