



# **Bath Shower Mixer**



# **Cross Top Bath Shower Mixer**

GENERAL INFORMATION					
Size	Pattern No.	Pack 1 Qty	Code	Barcode	Discontinued
NA	Bath Shower Mixer CP	1	350904	5013866076589	
NA	Bath Shower Mixer CP OP	1	350004	5013866044465	17/03/2008



DIMENSIONS (mm)						
Code	Description	A	В	С	D	Е
350904	CP MERCIA BATH SHOWER MIXER	93	70	113	180	37

## PRESSURE & TEMPERATURE

Bath Shower Mixer	Minimum Operating Pressure (bar)	Maximum Cold Working Pressure (bar)	Maximum Hot Working Pressure (bar)
CP MERCIA BATH SHOWER MIXER WITH KIT	0.1 bar	10.0 bar at temperatures up to 85oC	Not Suitable for Maximum Hot Working Pressure

Number	Component	Material
1	Body	Forged Brass with Chrome Plate
2	Backnut	Forged Brass
3	Anti-rotational washer	Polyethelene
4	Head	Brass Bar
5	Spindle	Brass Bar
6	Cross Tap	Forged Brass
7	Valve	Brass Bar
8	Gland	Brass Bar
9	Packing	Plastic
10	Seals	Rubber

# CARE & MAINTENANCE

# Care

To maintain the surface finish, simply wipe occasionally with a mild detergent on a soft damp cloth. Dry, using a soft cloth. Never use abrasive cleaners or chemical household cleaners and avoid contact with concentrated bleach.

No regular maintenance is required for this product.

In case of complete replacement Pegler recommend service valves should be fitted to the supply inlets.

For any further help or replacement parts please contact the Service Support Team on 0800 1560050.

## Regulations

It is important to ensure that the water supplies to your taps and mixers are connected in accordance with the water regulations (WRAS) requirements and good plumbing practice.

It is Pegler's recommendation and good plumbing practice that the supplies of hot and cold water to the bath mixer should be at equal (balanced) pressures in order to provide a consistent flow. Supplies should be from a common source, either mains or tank fed. If supplies are not equal pressures then non return valves (801 check valves), (not supplied) should be fitted in each inlet supply line.

The outlet of the fitting must be at least 25mm above the spill over level of the bath.

It is recommended that in all new and refurbishment installations a thermostatic mixing valve should be installed on the hot inlet supply. The thermostatic mixing valve is designed to prevent scolding when using the hot water supply.

## **Luxury Taps and Mixers**

## Pegler Yorkshire Customcare 10 Year Guarantee - Terms and Conditions

Product are subject to a 10 year guarantee that is between Pegler Yorkshire and the final purchaser of the product.

The guarantee is subject to proof of purchase being supplied.

This guarantee does not affect any statutory rights the consumer may have in law.

The guarantee covers manufacturing or material defects and does not cover parts subject to normal wear and tear.

Finishes other than chrome are covered for a period of 3 years only and the guarantee on the finish is subject to the cleaning instructions being followed.

The guarantee is not applicable where the product is fitted contrary to the conditions in the fitting instructions.

Abusive behaviour and accidental damage to the product are not covered by this guarantee.

The extent of this liability is limited to the cost of the replacement of the defective item and not to fitting or consequential damages.



**WRAS**