



Safeguard T100 Care

thermostatic electric shower



Dimensions given are approximate



**BEAB
CARE**

RNIB

Operating Features

- Endorsed by the RNIB
- Unique three stage thermostatic performance
- Adjustable timed shutdown
- Adjustable maximum temperature stop
- Provision for a connection to a level access waste pump
- Phased shutdown
- Large push button Start/Stop
- Low pressure indicator
- Extended riser rail
- 2m hose
- Ergonomic rub clean showerhead - 5 spray pattern

Finish	Power	Code
White/Chrome	8.5 kW	C100SG08WC

Temperature Control	Thermostatic
Power Ratings	8.5 kW
Inlet Connections	15mm compression
Water Entry Points	Top, bottom, back (right hand side of unit)
Cable Entry Points	Top, bottom, back (right hand side of unit)
Outlet Connection	1/2" BSP
Plumbing System Compatibility	Mains cold water only
Minimum Running Pressure/Flow	0.5 Bar at 8l/min*
Maximum Static Pressure	10 Bar
Surface Mounted Only	
Approvals, Complies with	BEAB, BEAB Care, RNIB, CE, BSI kite mark
Guarantee	2 years

*Recommended minimum running pressure/flow for full performance 1 Bar @ 8 l/min