


sola thermostatic shower valves

TMV3 approved


range of shower fittings available



sola thermostatic shower valve - concealed





sola thermostatic shower valve - concealed



sola thermostatic shower valve - exposed



sola thermostatic shower valve - exposed



thermostatic shower valve, TMV3

Concealed with elbow **SF1155CP**
Exposed **SF1152CP**

applications

Commercial, Domestic, Education, Healthcare, Hotels & Leisure, Other, Security, Special Needs.

BREEAM compliant when fitted with the below sola shower fittings.

approvals

TMV3
HTM64 - TM1 (Concealed only)
W.R.A.S.



finish

Chrome plated CP.

installation

Inlet connections 15mm.
Outlet connections 2 x 1/2" BSP.
Minimum operating pressure 0.2 bar.
Maximum rec. operating pressure 5 bar.
Minimum static pressure 10 bar.

flow rates

See relevant shower fittings below.

note Pre-set factory temperature setting 43°C. Supplied with full service and maintenance instructions. Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems.

recommended fittings

sola shower: **SF1251CP**
rail, hose & head **SF1202CP**
fixed head **SF1253CP**
vandal resistant head

All measurements shown are in millimetres. drawing sizes are not to scale.
to specify/order: Please use the 8 character reference shown above.

Lawton Road, Alsager, Stoke-on-Trent ST7 2DF, UK
Tel: +44(0) 1270 879777 Fax: +44(0) 1270 873864
www.twyfordbathrooms.com UK Technical Helpline Tel: 0870 840 0437 Fax: 0870 840 0438

Twyford
bathrooms